



Sarex Chemicals

(A Divn. Of Saraf Chemicals Pvt. Ltd.)

501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W),Mumbai 400 058. INDIA

Phone +91 22 42184218

Fax +91 22 42184350

Email : tcmktg@sarex.com

URL www.sarex.com

PRODUCT LITERATURE

SARAGUARD-MOSQ

(Mosquito repellent agent)

(Mosquito repellent agent)

Product Information

Saraguard-MOSQ is a microencapsulated mosquito and insects repellent for long lasting delivery of repellent protection on fabric surface. Saraguard-MOSQ is a unique product in a microcapsule form to repel mosquitoes. It is suitable for all substrates. Saraguard-MOSQ passes WHO cone test. Fabric finished with Saraguard-MOSQ does not have any odour.

Key Features & Benefits

Key Features

Speciality product

Long lasting & durable

Benefits

- Micro encapsulated mosquito repellent
- Prevents vectors such as mosquitoes ticks etc., from landing / biting

Durable to home laundering

General Characteristics

Physical appearance : Colourless to straw white liquid

Ionic nature : Nonionic

pH of 1% solution : 6.5 +/- 1

Miscibility : Miscible with water

Compatibility : Compatible with cationic, anionic and nonionic products

Stability : Stable to dilute acids and dilute alkalies

Application

Padding process:

Saraguard-MOSQ* : 100-120 g/l

Saralink-ULF : 30-40 g/l

Pick-up : 70-80%

Bath pH : 5-6



Sarex Chemicals

(A Divn. Of Saraf Chemicals Pvt. Ltd.)

501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W),Mumbai 400 058. INDIA

Phone +91 22 42184218 Fax +91 22 42184350

Email : tcmktg@sarex.com URL www.sarex.com

PRODUCT LITERATURE

SARAGUARD-MOSQ

Drying & Curing : 150-180 deg.C

* Dosage of Saraquard-MOSQ depends on home launderings required

Exhaust Proces: (Garment m/c, winch, low turbulence m/c)

Saraguard-MOSQ : 10-12%

Saralink-ULF : 3-4%

Temp. : 30-40 deg.C

Time : 20-30 min.

Note:

Product has tendency to separate on extended storage. Stir well before use.

Precautions

Storage : Store in cool, ventilated shed away from heat and direct sunlight.Storage temperature should not exceed 35 deg C.Close lids firmly to avoid contact with air and moisture.

Shelf Life : 8 months from the date of manufacturing, if stored under controlled conditions.

[The above information is given in good faith and is without warranty]
[Prod.Code :PY218 | Last Upd. On : 18/06/16] [PP]

This is a computer generated report. Hence not signed.