



Sarex Chemicals

(A Divn. Of Saraf Chemicals Pvt. Ltd.)

501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W),Mumbai 400 058. INDIA

Phone: +91 22 42184218

Fax : +91 22 42184350

Email : tcmtkg@sarex.com

URL : www.sarex.com

PRODUCT LITERATURE

SARADYE-429 (MOD)

Product Information

Saradye-429 (MOD) is a speciality product to improve fastness to chlorinated pool water. It is highly efficient on polyamide fabrics dyed/printed with acid dyes. Saradye-429 (MOD) has minimum effect on light fastness and tone of the treated material. Saradye-429 (MOD) does not affect the original handle and absorbency of fabric.

Key Features & Benefits

Key features -----	Benefits -----
Fastness	- Improves colour fastness upto 100 ppm available chlorine - Improves water contact and wash fastness
Handle	Does not affect the original handle and absorbency of fabric
Versatile	Can be applied by exhaust as well as pad application

General Characteristics

Physical appearance	: Colourless clear Liquid
Ionic Nature	: Nonionic
pH of 1% solution	: 6 +/- 1
Miscibility	: Miscible with water
Compatability	: Compatible with anionic, cationic and nonionic products
Stability	: Stable to dilute acids and dilute alkalies

Application

After thorough soaping and neutralisation, treat the material with below recipe.

Padding process

Saradye-429 (MOD) : 25-35 g/l (depending on chlorine content in water)

pick-up : 65-70%



Sarex Chemicals

(A Divn. Of Saraf Chemicals Pvt. Ltd.)

501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W),Mumbai 400 058. INDIA

Phone: +91 22 42184218

Fax : +91 22 42184350

Email : tcmtkg@sarex.com

URL : www.sarex.com

PRODUCT LITERATURE

SARADYE-429 (MOD)

Bath pH : 5.0-5.5
Dyring : 140-160 deg.C

Exhaust process

Saradye-429 (MOD) : 2.5-3.5% (depending on chlorine content in water)

Bath pH : 5.0-5.5
Bath Temp. : 50 deg.C
Time : 15-20 mins.

Precautions

Storage : Store in cool, ventilated shed away from heat and direct sunlight.Storage temperature should not exceed 35 deg C.Close lids firmly to avoid contact with air and moisture.

Shelf Life : 8 months from the date of manufacturing, if stored under controlled conditions.

[The above information is given in good faith and is without warranty]
[Prod.Code :PY859 | Last Upd. On : 26/11/15] [MOLL]

This is a computer generated report. Hence not signed.