

Sarex Overseas (A division of Sarex Organics Pvt. Ltd.)



Corporate Office: 501-502, Waterford, C Wing, Juhu Lane, Andheri (W), Mumbai - 400 058, India.

Phone: +91(22) 6128 5566 / 4218 4218, **Fax:** +91(22) 4218 4350.

Web: www.sarex.com • Email: fchem@sarex.com

APPOLO-400

1. STRUCTURE

$$C_{12}H_{25}$$

$$OH$$

$$C_{13}H_{27}$$

2. PRODUCT NAME & DETAILS

2-[4-[(2-Hydroxy-3-dodecyloxypropyl)oxy]-2-hydroxyphenyl]-4,6-bis(2,4-dimethylphenyl)-1,3,5 -triazine & 2-[4-[(2-Hydroxy-3-tridecyloxypropyl)oxy]-2-hydroxyphenyl]-4,6-bis(2,4-dimethylphenyl) -1,3,5-triazine (Appolo-400)

Product Code : 001356

CAS No. : 153519-44-9

HS Code : 3812.39.90

Molecular formula : $C_{81}H_{108}N_6O_8$

Molecular weight : 1293.8

3. REGULATORY INFORMATION

Chemical name	Common names and synonyms	CAS number	EC number
Appolo-400		153519-44-9	410-560-1
European Inventory of Existing Commercial Chemical Substances (EINECS)		Not Listed	
EC Inventory		Listed	
United States Toxic Substances Control Act (TSCA) Inventory		Listed	
China Catalog of Hazardous chemicals 2015		Not Listed	
Chinese Chemical Inventory of Existing Chemical Substances (China IECSC)		Listed	
Korea Existing Chemicals List (KECL)		Not Listed	
Canadian Domestic Substance List (DSL)		Listed	
Canadian Non-Domestic Substance List (NDSL)		Not Listed	
Japanese Existing and New Chemical Substances Inventory (ENCS)		Not Listed	

Disclaimer



Sarex Overseas (A division of Sarex Organics Pvt. Ltd.)



Corporate Office: 501-502, Waterford, C Wing, Juhu Lane, Andheri (W), Mumbai - 400 058, India.

Phone: +91(22) 6128 5566 / 4218 4218, **Fax:** +91(22) 4218 4350.

Web: www.sarex.com • Email: fchem@sarex.com

APPOLO-400

4. SPECIFICATION

Physical Appearance : Yellow To Slight Orange Viscous Liquid

Clarity of solution : Clear Solution

Identification : Complies

Color of Solution 460 nm (%) : NLT 94%

Color of Solution 500 nm (%) : NLT 97%

Assay : NLT 83%

5. APPLICATION

- It can be used in industrial paints and automotive paints with high thermal stability and durability requirements.
- It is a UV absorber that does not cross-react with other components of the system and was developed specifically for amine-catalyzed or metal-catalyzed coating systems.
- Environmental durability, suitable for coatings used in extremely harsh conditions.
- Low migration, high concentration and high efficiency.
- Good light stability, effective long life.

6. HAZARD CLASSIFICATION : Hazardous Substance (UN No. 3092)



Irritant



Flammable

7. ANNUAL CAPACITY : 200 MT.

8. STORAGE CONDITION

: Store in closed container at ambient temperature. Avoid direct sun light.

9. PACKING DETAILS : 160 kg in GI drum.

10. SHELF LIFE : 3 years.