

501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W),Mumbai 400 058. INDIA

Phone: +91 22 42184218 Fax: +91 22 42184350

Email: tcmktg@sarex.com

URL : www.sarex.com

PRODUCT LITERATURE

SARAFINISH-SS

Product Information

Sarafinish-SS is a wash fast finishing agent for all types of fibres in any form i.e knits,wovens or garments. Finishing with Sarafinish-SS gives crisp dry handle to the treated material. Sarafinish-SS also improves resistance to pilling and gives anti-snag finish.

By using Sarafinish-SS, seam slippage tendencies are reduced. Sarafinish-SS can be applied by exhaust as well as pad application. The product can be applied in combination with water-repellent agents and with resins. Finish obtained with Sarafinish-SS is basically resistant to washing & dry cleaning.

Key Features & Benefits

Key Features	Benefits			
Universal	Suitable for all natural, synthetic fibres and blends			
Versatile	Can be applied by exhaust and pad			
Multifunction	Anti-pilling, Anti-slip, Anti-snag finish can be developed			
Compatibility	Can be used with resins as well as fluorochemicals			

General Characteristics

Physical appearance	:	Straw white to milky white liquid				
Ionic nature	:	Cationic				
pH of 1% solution	:	5 +/- 1				
Miscibility	:	Miscible with water				
Compatibility	:	Compatible with cationic & nonionic				
		products, water repellent agents, softeners and resins				
Stability	:	Stable to hard water & dilute acids. Not stable to alkalies, phosphates & excess sulphates.				

Application

1. Exhaust Application:

Depending on the end use requirements,



501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W),Mumbai 400 058. INDIA

Phone: +91 22 42184218 Fax: +91 22 42184350

Email: tcmktg@sarex.com

URL : www.sarex.com

PRODUCT LITERATURE

SARAFINISH-SS

0.5-4% of Sarafinish-SS pH 5, treat at 35-40 deg.C for 20-40 min.

2. Pad Application:

5-20 g/l Sarafinish-SS Pad at pH-5, 60-70% pick-up, dry/cure as per the normal finishing conditions.

Precautions

Storage	: St	ore in	cool, v	ventilate	d shed	away	from
	he	at and d	direct su	unlight.S	torage	temper	ature
	sh	ould not	t exceed	35 deg C	.Close	lids f	firmly
	to	avoid	contact	t with	air an	nd mois	sture.

Shelf Life : 8 months from the date of manufacturing, if stored under controlled conditions.

[The above information is given in good faith and is without warranty] [Prod.Code :PY200 | Last Upd. On : 22/07/14] [PP]

This is a computer generated report. Hence not signed.