

501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W),Mumbai 400 058. INDIA

Phone +91 22 42184218 Fax +91 22 42184350

Email : tcmktg@sarex.com URL www

URL www.sarex.com

# PRODUCT LITERATURE

# SARALINE-FI (CONC)

### Product Information

Saraline-FI (Conc) is a flakes form dispersing, wetting and emulsifying agent. Saraline-FI (Conc) keeps the insoluble dye particles in fine dispersion and prevents redeposition on the substrate, therefore, it is useful in the dyeing of disperse dyes, acetate dyes, acid dyes, chrome dyes and naphthol dyeing. Saraline-FI (Conc) also helps in smooth running of the pad bath hence preventing roller build up.

## Key Features & Benefits

Key Features	Benefits
Multipurpose	Use as levelling, dispersing, emulsifying agent, hence less inventory
Versatile	Suitable for cotton, polyester, wool, silk & nylon
Good dispersing / emulsifying action	Can prevent silicone spots in finishing of longer batches under adverse conditions

## General Characteristics

Physical appearance	:	White flakes
Ionic nature	:	Non-ionic
pH of 1% solution	:	7 +/-1
Miscibility	:	Miscible in hot water
Compatibility	:	Compatible with anionic, cationic and
		non-ionic products.
Stability	:	Stable to dilute acids & dilute alkalies.

## Application

- Exhaust Dyeing of Polyester and blends and polyamide, Wool and silk.
  0.2-0.4 g/l Saraline-FI (Conc) As a levelling and dispersing agent
- 2. Thermosol Dyeing of Polyester and Blends



501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W), Mumbai 400 058. INDIA

Phone +91 22 42184218 Fax +91 22 42184350

Email:tcmktg@sarex.com

#### URL www.sarex.com

# **PRODUCT LITERATURE**

#### SARALINE-FI (CONC)

2-4 g/l Saraline-FI (Conc) in pad liquor improves bath stability, ensures uniform dyeing and improves colour yield.

- 3. Roller build up 0.1-0.2 g/l addition of Saraline-FI ensures smooth running of pad bath thus preventing roller build up.
- 4. Pigment Printing 0.2-0.4% Saraline-FI (Conc) Can be used as an emulsifier in preparation of emulsion thickening for pigment printing.
- 5. Finishing of cotton, polyester/cellulosics, polyester/wool blends: Addition of 0.4-1.0 g/l Saraline-FI (Conc) improves finishing bath stability under adverse conditions such as incompatible recipe, longer storage time, water containing TDS, etc.

## Instructions For Dilution

20% dilution of Saraline-FI (Conc).

Take 80 parts of DM water at 80 deg.C and to this add slowly 20 parts of Saraline-FI (Conc) under constant stirring at 150-220 rpm using paddle stirrer. Continue stirring till product cools down to room temperature and it becomes a homogeneous liquid.

stored under controlled conditions.

### Precautions

Storage	: Store in cool, ventilated shed away from
	heat and direct sunlight.Storage temperature
	should not exceed 35 deg C.Close lids firmly
	to avoid contact with air and moisture.
Shelf Life	: 9 months from the date of manufacturing, if

[The above information is given in good faith and is without warranty] [ Prod.Code : PY807 | Last Upd. On : 08/05/15 ] [MOLL]

This is a computer generated report. Hence not signed.