

501 Waterford, C Wing, C.D.Barfiwala Marg (Juhu Lane), Andheri(W), Mumbai 400 058. INDIA

Phone - +91 22 42184218 **Fax** +91 22 42184350 Email tcmktg@sarex.com URL www.sarex.com

PRODUCT LITERATURE SARASOFT-1371

Product Information

Sarasoft-1371 is developed to give excellent inner softness to fabric. It imparts excellent softness on cotton, polyester, wool and their blends.

It can be applied by pad application and by exhaust in garment machines.

Key Features & Benefits

Key Features Benefits

Non-yellowing / Specially for whites and light shades

No shade change

No shade change

Shade will be unchanged before and after finishing which is normally

not achieved.

Excellent inner softness

and surface smoothness

Ideal for P/V suitings and cotton bottom weight

General Characteristics

Physical appearance Straw white /colourless to yellowish liquid

Ionic nature Nonionic 5 + / - 1pH of 1% solution

Miscibility Miscible with water

Compatibility Compatible with anionic, nonionic and cationic products.

Stability Stable to dilute acids and dilute alkalies

Application

1. For 100% Cotton Bottom Weight:

Sarasoft-1371 20-30 g/l Sarasoft-1367 10-20 g/l Sarasoft-I 20-30 g/l Sarasoft-EP 20-30 g/l

pH 5-6, pad with 65-70% pick-up, dry at 130-160 deg.C

2. For P/V (67/33) suiting:

Document: L007010.Docx

Sarasoft-1371 10-20 g/l Sarasoft-1367 10-20 g/l 20 Sarasoft-I g/l

pH 5-6, pad with 65-70% pick-up, dry at 130-160 deg.C

[The above information is given in good faith and is without warranty]

This is a computer generated report. Hence not signed.

Printed by :Jeevanprabha.Pai

Last Updated on: 07-09-2019 14:41

Page: 1 of 2



501 Waterford, C Wing, C.D.Barfiwala Marg (Juhu Lane), Andheri(W), Mumbai 400 058. INDIA

PRODUCT LITERATURE SARASOFT-1371

3. For 100% Polyester filament fabric

Sarasoft-1371 3-10 g/l Sarasoft-I 5-10 g/l pH 5-6, pad with 65-70% pick-up, dry at 130-160 deg.C

4. For Exhaust Application on garments:

1-3% Sarasoft-1371(owf) depending on requirements. pH 4.5-5.0, at 30-40 deg.C for 10-20 min.

Precautions

Storage Store in cool, ventilated shed away from heat and direct sunlight. Storage

temperature should not exceed 35 deg c. Close lids firmly to avoid contact with air

and moisture.

Shelf Life 9 months from the date of manufacturing, if stored under controlled conditions.

[The above information is given in good faith and is without warranty]

This is a computer generated report. Hence not signed.

Document : L007010.Docx Printed by :Jeevanprabha.Pai

Last Updated on : 07-09-2019 14:41

Page : 2 of 2