



Sarex Chemicals

(A Divn. Of Saraf Chemicals Pvt. Ltd.)

501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W),Mumbai 400 058. INDIA

Phone +91 22 42184218 Fax +91 22 42184350

Email tcmtkg@sarex.com URL www.sarex.com

PRODUCT LITERATURE

TEXPRINT-PP

Product Information

Texprint-PP is a new generation concentrated silicone based softener which imparts soft and dry handle to pigment printed fabrics. It also improves fastness properties of pigment printed fabrics. It is to be added in the print paste.

Key Features & Benefits

Key Features

Very good softness

Improves brilliancy and fastness of prints

Benefits

Product can be added in the print paste

Dry rub fastness is achieved alongwith brighter prints

General Characteristics

Physical appearance : Colourless to pale yellow viscous liquid

Ionic nature : Nonionic

pH of 1% solution : 6 +/- 1

Miscibility : Miscible with water

Compatibility : Compatible with anionic, cationic and nonionic products

Stability : Stable to dilute acids and dilute alkalies

Application

Texprint-PP : 5-20 g/kg (of the pigment print paste)

Precautions

Storage : Store in cool, ventilated shed away from heat and direct sunlight. Storage temperature should not exceed 35 deg.C. Close lids firmly to avoid contact with air and moisture

Shelf Life : 9 months from the date of manufacturing, if stored



Sarex Chemicals

(A Divn. Of Saraf Chemicals Pvt. Ltd.)

501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W),Mumbai 400 058. INDIA

Phone +91 22 42184218 Fax +91 22 42184350

Email tcmtg@sarex.com URL www.sarex.com

PRODUCT LITERATURE

TEXPRINT-PP

under controlled conditions.

[The above information is given in good faith and is without warranty]
[Prod.Code :L009732 | Last Upd. On : 18/01/2020] [MOLL]

This is a computer generated report. Hence not signed.