

501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W), Mumbai 400 058. INDIA

Email tcmktg@sarex.com URLwww.sarex.com

PRODUCT LITERATURE

FLAMGUARD-PS

Product Information

Flamguard-PS is a durable flame retardant for 100% polyester, applicable by exhaust application. Flamguard-PS is halogen free. Fabric finished with Flamguard-PS shows minimum effect on shade and posses good fastness to home laundering and dry cleaning. Flamguard-PS does not have any effect on the drape of the treated fabric. Flamguard-PS has low volatility and does not lead to fogging. It is suitable for protective work wear, furnishing fabrics, curtains and automotive textiles made from 100% polyester and polyester rich blend. It is also applicable by spray method.

Key Features & Benefits

Key Features Benefits

Durable to home laundering and

dry cleaning

Feel Handle of fabric not impaired

General Characteristics

Physical appearance: Milky white to off white viscous liquid

Miscibility : Miscible with water

Compatibility : Compatible with anionic and nonionic

products

Stability : Stable to dilute acids and dilute alkalies

Application

1. Exhaust Application :

5-10% Flamguard-PS.

Temp-130 deg.C.

It is applied during dyeing process with disperse dyestuff

Flamguard-PS can pass following Tests:

- i) FMVSS302
- ii) NFPA-701



501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W), Mumbai 400 058. INDIA

Email tcmktg@sarex.com URLwww.sarex.com

PRODUCT LITERATURE

FLAMGUARD-PS

iii) BS-5852

Note: Flamquard-PS shows separation on standing stir well before use.

Precautions

Storage : Store in cool, ventilated shed away from

heat and direct sunlight. Storage temperature should not exceed 35 deg C.Close lids firmly to avoid contact with air and moisture.

Shelf Life : 9 months from the date of manufacturing, if

stored under controlled conditions.

[The above information is given in good faith and is without warranty]

[Prod.Code : L004732 | Last Upd. On : 30/07/19] [PP]