

501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W),Mumbai 400 058. INDIA

Phone +91 22 42184218 Fax +91 22 42184350

Email tcmktg@sarex.com URLwww.sarex.com

PRODUCT LITERATURE

FLUID-828

Product Information

Fluid-828 is a oil-in-water emulsion polydimethylsiloxane with medium viscosity. It is shear stable. It exhibits excellent wetting properties.

Key Features & Benefits

Key Features -----Hydrophilic

Easy polising

Benefits -----Excellent wetting property

Improves brightness

General Characteristics

Physical appearance: Off White liquidIonic nature: Non-ionicpH of 1% solution: 6 +/- 1Miscibility: Miscible with waterCompatibility: Compatible with anionic, cationic and nonionic productsStability: Stable to dilute acids and dilute alkalies

Application

```
Padding process
-----
Dosage* : 5-20 g/l
Pick-up : 65-70%
Bath pH : 5.0-6.0
Drying & : 130-160 deg.C
curing 30-45 secs.
```

Exhaust process

Dosage*	:	0.5-2%
Bath pH	:	5.5-6.0
Bath Temp.	:	35-40 deg.C
Time	:	20-30 mins.



501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W),Mumbai 400 058. INDIA

Phone +91 22 42184218 Fax +91 22 42184350

Email tcmktg@sarex.com URLwww.sarex.com

PRODUCT LITERATURE

FLUID-828

Precautions

Storage : Store in cool, ventilated shed away from heat and direct sunlight. Storage temperature should not exceed 35 deg C. Close lids firmly to avoid contact with air and moisture.

Shelf Life : 9 months from the date of manufacturing, if stored under controlled conditions.

[The above information is given in good faith and is without warranty]

[Prod.Code :L010755 | Last Upd. On :14/12/2021] [PVR]